

## AGRILUB SAE 15W40

**Description :** A multipurpose oil “S.T.O.U. ” combined for the hydraulic systems, transmissions including or not immersed brakes (with oil bath) and engines of tractors and some stationary machines.

**Application :** Generally conceived for the gear boxes and differentials with immersed brakes, hydraulically-operated gear boxes or derived hydraulic system, circuits of raising, hydraulic fluid powers and driving.

### **Specifications :**

- **ENGINE**
- API : CF-4/SF
- ACEA E3
- **STOU**
- FORD M2C 159B
- NEW HOLLAND 8200920/3 - NH 024C – NH 330B
- FIAT AF 87
- JOHN DEERE J27C
- MASSEY FERGUSON M1139, 1144
- **TRANSMISSION**
- API : GL-4
- ZF TE ML 06B
- ALLISON C-4
- **UTTO**
- JOHN DEERE J27C
- MASSEY FERGUSON M1139, 1143



# Product information

Quali industries (Belgium)

Technical Customer Service



## Properties:

- Universal oil for tractors and all workshop materials.
- Utilization in tropical climate and by freezing temperatures.
- Reduces noise due to working of immersed brakes
- Less failures possible because one product is used.
- Good protection against wear and corrosion.

## Typical analyses :

Density at 15°C	0,870	Color	L 4.5
Viscosity at 100°C	13,0 cSt	Viscosity at 40°C	102,0 cSt
Viscosity index	Min. 120	Flash point	215°C
T.B.N. mg. KOH/g	10,0	Pour point	-30° C

These values are given as an indication, it acts of average values.

